The invention claimed is:

- 1. An omnidirectional two dimensional imaging apparatus comprising:
- (a) A truncated convex reflective mirror that reflects an image of substantially hemispherical scene;
- (b) An imaging sensor means positioned to receive said omnidirectional images; whereby images with wide field-of-view of substantially hemispherical scene from a single viewpoint can be obtained.
- 2. An apparatus as recited in claim 1, wherein the reflective mirror is a substantially hyperbolic reflective mirror whereby the substantially hemispherical omnidirectional images with single viewing center can be obtained.
- An omnidirectional stereo camera apparatus comprising of a pair of optically aligned omnidirectional two dimensional imaging systems as recited in claim 1 whereby the stereo omnidirectional images can be obtained.
- An omnidirectional stereo camera apparatus comprising of a pair of optically aligned omnidirectional two dimensional imaging systems as recited in claim 2 whereby the stereo omnidirectional images can be obtained.
- 5. An omnidirectional three dimensional camera apparatus comprising:
- An omnidirectional two dimensional imaging systems as recited in claim 1;
- (b) An omnidirectional structured light projection means;

1,50

- whereby the three dimensional measurement of the surrounding objects in the omnidirectional scene can be obtained.
  - 6. An omnidirectional three dimensional camera apparatus comprising:
  - (c) An omnidirectional two dimensional imaging systems as recited in claim 2;
  - (d) An omnidirectional structured light projection means;

whereby the three dimensional measurement of the surrounding objects in the omnidirectional scene can be obtained.

## **Patent Application Documents**

- Method and Apparatus for Omnidirectional Stereo Imaging [54]
- [75] Inventor: Zheng Jason Geng, Rockville, Maryland, U.S.A.
- [73] Assignee: none.
- [21] Appl. No.
- Filed: [22]
- [51] Int. Cl G02F 001/35
- [52] U.S. Cl 348/036;
- Field of Search: 348-36,38,143,147,117; 396-351,21,427; [58]
- [56] References Cited:

## U.S. REFERENCES: (No patents reference this one)

(10 patonts reference than one)			
US Patent Documents			
<b>4549208</b>	Kamejima et al. 10/1985		Picture processing apparatus
5185667	Zimmermann	2 /1993	Omniview motionless camera orientation system
<b>5359363</b>	Kuban et al.	10 /1994	Omniview motionless camera surveillance system
5563650 and a method	Poelstra d and device for	10/1996 consulting pane	Method and device for producing panoramic images, oramic images
5760826	Nayar	6/1998	Omnidirectional Imaging Apparatus

## Other Publications

:[]

- Wood, R.W., Fish-eye view and vision under water, Philosophical Magazine, 12(Series (1) 6):159-162,1906
  - Miyamoto, K, Fish-eye Lens, J. Optical Soc. America, 54(8),:1060-1061,1964 (2)
  - (3) Oh,S.J, and Hall,E., Guyidance of a Mobile Robot using an Omni-directional Vision Navigation System, Proc. SPIE,852:288-300, Nov.,1987
  - Kuban, D.P., et al, Omniview Motionless Camera Surveillance System, US Patent, No. (4) 5,359,363, Oct. 1994
  - Chen, S.E., QuickTime VR An image based approach to virtual environment navigation, (5) Computer Graphics: Proc. Of SIGGRAPH 95, p29-38, 1995
  - McMillam, L, and Bishop, G., Plenoptic Modeling: An image-based rendering system, (6) Computer Graphics: Proc. Of SIGGRAPH 95, p38-46, 1995
  - Zheng, J.Y., and Tsuji, S, Panoramic representation of scene for route understanding, Proc. (7) 10 Int. Conf. Pattern Recognition, 1:161-167, 1990
  - Krishnan, A, and Ahuja, N., Panoramic image acquisition, Proc. Of IEEE Conf. Computer (8) Vision and Pattern Recognition (CVPR-96), p379-384,1996